

MP50 Vacuum Diaphragm Pump



Pump specifications:

Туре	.MP50 diaphragm pump
Max. air capacity	.50 m3/h (29 CFM)
Max. vacuum	.8.5 m (29 inHg)
Diaphragm/valves	.Rubber
Diaphragm covers	.Aluminium
Required power	.2.2 kW (3 Hp)
Optimal speed	.1500 rpm
Oil capacity	.0.6 liter (0.63 qt)
Type of oil	.15W40
Colour	.RAL7016
Dry weight	.30 kg (66 lbs.)

MP vacuum diaphragm pump

The MP range of pumps with air handling capacities of 50 m3/h or 100 m3/h – depending on the model – has been designed with a clear focus on reliability, efficiency and durability. This mechanical diaphragm pump quickly prime and re-prime, is water resistant and oil-spill free.

Complete package designed & built by BBA Pumps

- Complete in-house design & production
- Over 60 years of experience in the market
- Extensive testing facility in-house
- Contemporary & functional design
- Durable & eco-friendly materials
- Custom builds available

After sales service & product support

- Single supplier for parts, spares & accessories
- Dedicated customer help-desk (24h service)
- Dedicated service department in-house
- Global parts distribution network
- Optional global on-site servicing
- Extensive training options available (technical & commercial), on-site or in-house







